

REVERSIBLE PLATE COMPACTOR
可逆式双向平板夯 >>>



FPC160

- 特点:
- ◆可逆式双向平板夯，手柄控制机械前进和后退。
 - ◆FPC160 plate compactor is reversible plate compactor, operators can control the machine forward and backward by clutch handle.

技术参数/Specification:

型号 Model	FPC160	
重量 Weight	160kg	
外形尺寸 Dimension	L865xW550xH1120mm	
夯板尺寸 Plate size	L650xW500mm	
压实力 Centrifugal force	30kn	
振动频率 Vibration frequency	5500(92)rpm/hz	
前进速度 Speed	20-23m/min	
动力 Engine	四冲程风冷汽油机 Air-cooled, 4-cycle, Gasoline	
型号 Type	本田 GX160 Honda GX160	力帆 168 Lifan
最大输出功率 Max.output	4.0kw/5.5hp	4.8kw/6.5hp
最大转速 Max.speed	3600rpm	
汽油箱容量 Fuel tank	3.6L	

REVERSIBLE PLATE COMPACTOR
<<< 可逆式双向平板夯

FPC330

- ◆ Forward & reverse, as well as on-spot compaction
- ◆ Easy-to-reach located controls
- Large shock mounts reduce vibration to the handle
- ◆ Heavy-duty shock mounts reduce vibration to the upper deck
- ◆ Wear-resistant base plates extend life, open design reduces dirty building
- ◆ Centrally-located lifting bar allows easy transportation in and out of trenches
- ◆ Semi-covered protection cage protects the plate from accidental job-site damage



技术参数/Specification:

型号 Model	FPC330
动力 Engine	汽油、本田390 Petrol, Honda GX390
功率 Power	13hp/9.5kw
重量 Weight	250kg
激振力 Centrifugal	38kn
激振频率 Vibrating Frequency	4810rpm
行走速度 Max Travel Speed	15m/min
夯板尺寸 Plate size L x W	83 x 64cm



Especially additional air filter system



Electric starter system